

B06 Entgratringe *Deburring Rings, Fraises modulables d'ébavurage, Anello per smussare*

Fräswendeplatten und Schnittdaten

Milling inserts and parameters, Plaquettes de fraisage et paramètres, Inserti e parametri di taglio

			HT50 (code 22) 	TA50 (code 2) 	Ti20 (code 1) 	KT28 (code 23) 	K15M (code 8) 		
	JMB06-41R08- 15,6x10,0x3,18 R0,8 H M 	Order- No.	B06A-DS22						
	f_z [mm]		0,20 (0,10-0,30)						
	JMB06-41AR08- 15,6x10,0x3,18 R0,8 S 	Order- No.		B06A-CR02					
	f_z [mm]			0,20 (0,10-0,30)					
	JMB06-41AR08- 15,6x10,0x3,18 R0,8 U 	Order- No.					B06A-BJ08		
	f_z [mm]						0,20 (0,10-0,40)		
	JMB06-42R08- 15,6x10,0x3,18 R0,8 H M 	Order- No.	B06B-FA22		B06B-HC01	B06B-GB23			
	f_z [mm]		0,20 (0,10-0,30)		0,20 (0,10-0,30)	0,20 (0,10-0,30)			
	JMB06-42AR08- 15,6x10,0x3,18 R0,8 S 	Order- No.	B06B-CZ22		B06B-EZ01				
	f_z [mm]		0,20 (0,10-0,30)		0,20 (0,10-0,30)				
	JMB06-42AR08- 15,6x10,0x3,18 R0,8 U 	Order- No.					B06B-DW08		
	f_z [mm]						0,20 (0,10-0,40)		
			10	10	10	10	10		

B06 Entgratringe *Deburring Rings, Fraises modulables d'ébavurage, Anello per smussare*

Fräswendeplatten und Schnittdaten

Milling inserts and parameters, Plaquettes de fraisage et paramètres, Inserti e parametri di taglio

V _c [m/min]	Stahl Steel Acier Acciaio	Rostfrei Stainless Acier inoxydable Inossidabile	Guss Cast iron Fonte Ghisa	NE-Metalle Non-ferrous metals Non ferreux Metalli non ferritici	Hochwarmfest Highly heat-resistant Superalliages Resistente al calore	Gehärtet Tempered Aciers traités Temprato
HT50	220 (160 - 300)	200 (100 - 300)	240 (200 - 300)			
TA50	220 (160 - 300)	200 (100 - 300)	240 (200 - 300)			
Ti20	250 (220 - 280)	220 (180 - 300)	240 (180 - 350)			
KT28			260 (180 - 350)			80 (40 - 120)
K15M				400 (300 - 600)		

Ersatzteile *Spare parts, Pièces de rechange, Parti di ricambio*

	SS 4,0-1 (M = 3,2 - 3,3 Nm)		T 15		Fett <i>Grease, Graisse, Grasso</i>
---	---------------------------------------	---	-------------	---	---